



When taking measurements, consider:
 * = 250 mm (for motor replacement)
 ** = 162 mm with motor cover

Range of net opening dimensions of the door

	Min	Max
PL	900	4500
PH	1700	4600

PH	CL
≤3500	4000
>3500	6000

Key
 LT = Automation full width PL = Horizontal opening CL = Cable length
 HT = Automation full height PH = Vertical opening

Ditec Soft Reset

Technical datasheet

TECHNICAL SPECIFICATIONS	
Dimensions	Max. PL 4500 x PH 4600 mm Min. PL 900 x PH 1000 mm
Power supply	230 V single-phase 16 A - INVERTER-motion Frequency: 50/60 Hz Power of motor 0,6 kW Max. current for 24 Vdc accessories: 0,5 A IP degree for control board: IP55
Opening speed	Opening up to 2,3 m/s - closing up to 0,8 m/s
Service level	Life cycles : 500.000 - heavy duty Number of operations: 500 cycles/day - max 100 cycles/hour
Extra features	Manual opening : manual by crank operated from ground. Sealing : optional extra sealing to improve air tightness. Cablings: optional 6m cable for PH ≤ 3500 mm.
Frame	Standard: in hot galvanised steel. Optional: - AISI 304 stainless steel bright finishing or smooth finish oven-baked epoxy coating. - PVC column cover in black. - Galvanised steel upper casing cover. - Galvanised steel motor cover.
Recommended operating temperature	Motor + control board: - 5°C ÷ + 50°C Curtain: - 5°C ÷ + 50°C The limit of - 5°C is related to the PVC transparent windows. For further details on the use in cold environments, please contact your Ditec technical or sales support.

CURTAIN TECHNICAL SPECIFICATIONS													
Type of material	Standard, Non-tear and Food curtain: polyester fabric PVC coated on both sides. Insulated curtain: polyester fabric PVC coated on one side and foamed on the other. Double insulated: as previous one, but with foamed side covered with an additional layer of standard polyester PVC-coated curtain.												
Material thickness and weight	Standard curtain: 0,7 mm - 900 g/m ² Non-tear: 1,0 mm - 1300 g/m ² Insulated: 3,5 mm - 1300 g/m ² Double-insulated: 4,2 mm - 2200 g/m ² Food curtain: 0,5 mm - 700 g/m ²												
Vertical reinforcement strips	Clear PVC. Not applicable on insulated and double insulated curtain.												
Thermal Transmittance coefficient	Standard: 5,8 W/m ² K Non-tear: 5,5 W/m ² K Insulated and Double insulated: 4,0 W/m ² K												
Noise reduction	~ 12dB. Insulated: 17,5 dB												
Windows	clear PVC 1 mm, available: 980 x H 300 or 920 x H 1600 mm or full width x H920 Not applicable on double insulated curtain												
Available colours standard curtain	Similar to: <table border="0"> <tr> <td>Red RAL 3000</td> <td>Blue RAL 5010</td> </tr> <tr> <td>Orange RAL 2004</td> <td>Grey RAL 7038</td> </tr> <tr> <td>Yellow RAL 1021</td> <td>Green RAL 6026</td> </tr> <tr> <td>Cream RAL 1014</td> <td>White RAL 9010</td> </tr> <tr> <td>Light blue RAL 5012</td> <td>Black RAL 9005</td> </tr> <tr> <td>Dark grey RAL 7024</td> <td></td> </tr> </table>	Red RAL 3000	Blue RAL 5010	Orange RAL 2004	Grey RAL 7038	Yellow RAL 1021	Green RAL 6026	Cream RAL 1014	White RAL 9010	Light blue RAL 5012	Black RAL 9005	Dark grey RAL 7024	
Red RAL 3000	Blue RAL 5010												
Orange RAL 2004	Grey RAL 7038												
Yellow RAL 1021	Green RAL 6026												
Cream RAL 1014	White RAL 9010												
Light blue RAL 5012	Black RAL 9005												
Dark grey RAL 7024													
non-tear curtain	Yellow RAL 1004 Grey RAL 7046												
insulated and double insulated curtain	Blue RAL 5002 Grey RAL 7038												
food curtain	White RAL 9016												

© ASSA ABLOY - Ditec Soft Reset - Technical Datasheet - EN - V4.0 - 25/8/2021

STANDARDS AND CERTIFICATES	
Wind resistance class	EN 12424 (test EN 12444) : class 2: PL ≤ 3000 mm x PH 4600 mm class 1: 3000 < PL ≤ 4500 mm x PH 4600 mm
Air permeability	EN 12426 (test EN 12427) : NP
Water permeability	EN 12425 (test EN 12489) : NP
Closing door safety devices	EN 12453 (test EN 12445) : TOP Safety Pack: Self-testing SLE Safety Linear Encoder* + built-in IP67 photocells TOP T Safety Pack: Self-testing SLE Safety Linear Encoder* + IP65 sequential infra-red light barrier
Available Certifications	certificate n° DE/3382/09, Notified Laboratory n° 0497

* SLE - Safety Linear Encoder is a Ditec Entrematic patented system

Your Ditec dealer:

Dynaco Europe NV

Waverstraat 21
B-9310 Moorsel-Aalst
(Belgium)

T. +32 53 72 98 98

F. +32 53 72 98 50

M. Info.ditec.eu@ditecautomations.com

www.ditecdoor.com

Ditec is a world leading brand, offering high speed doors, traffic control automation and pedestrian door solutions since 1974. Marketing our products exclusively through professional distributors and installers, we promise our partners continuous product innovation, on-time logistics and full technical and commercial support. Ditec is part of the ASSA ABLOY Group, the world leader in access solutions. Every day, we help billions of people experience a more open world.